

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
23 December 2004 (23.12.2004)


PCT

(10) International Publication Number  
**WO 2004/111802 A2**

- (51) International Patent Classification<sup>7</sup>: G06F
- (21) International Application Number: PCT/US2004/009483
- (22) International Filing Date: 29 March 2004 (29.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/459,697 2 April 2003 (02.04.2003) US
- (71) Applicant (for all designated States except US): SICEL TECHNOLOGIES, INC. [US/US]; 3800 Gateway Center Boulevard, Suite 308, Morrisville, North Carolina 27560 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BLACK, Robert D. [US/US]; 203-8 Conner Drive, Chapel Hill, North Carolina
- (27514 (US). MANN, Gregory Glenwood [US/US]; 5437 Stewartby Drive, Raleigh, North Carolina 27613 (US). WIDENER, Steven R. [US/US]; 12929 Bold Run Hill Road, Wake Forest, North Carolina 27587 (US).)
- (74) Agent: MYERS BIGEL SIBLEY & SAJOVEC, P.A.; P.O. Box 37428, Raleigh, North Carolina 27627 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EB, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

*[Continued on next page]*

(54) Title: METHODS, SYSTEMS, AND COMPUTER PROGRAM PRODUCTS FOR PROVIDING DYNAMIC DATA OF POSITIONAL LOCALIZATION OF TARGET IMPLANTS



(57) Abstract: Systems for locating implanted in vivo sensor systems adapted for use with an external beam radiation therapy delivery source include: (a) an external solenoid member; (b) an articulated arm operatively associated with the external solenoid member, wherein, in operation, the articulated arm is configured to translate the solenoid; (c) a controller configured to direct the movement of the articulated arm, the controller being in communication with a power source configured to power the external solenoid; (d) at least one implantable sensor unit, wherein the at least one implantable sensor unit is configured to sense at least one predetermined parameter of interest in vivo, and wherein the at least one implantable sensor unit comprises a solenoid, and wherein, in operation, the sensor unit solenoid cooperates with the external solenoid to generate a magnetic coupling signal having a signal strength that varies based on the position of the external solenoid member relative to the implanted sensor unit; (e) a computer module in communication with the controller comprising computer program code that evaluates the coupling signal strength in relation to the position of the external solenoid and determines the position of the at least one sensor unit; and (f) an external reader configured to wirelessly communicate with the at least one implantable sensor unit to obtain data associated with the at least one predetermined parameter of interest.